



Programmable Relay Pack

# Model SWRi-4

## SPECIFICATION

The 'Aqualarm' SWRi-4 Programmable Relay pack is for connection to the i-Zone Mini control panel. The Relay pack is housed in an IP-54 rated ABS box. Connection to the Relay pack is via the Expansion port of the control panel. Four programmable relays are available in each pack, and each pack can be used for either switching of ancillary items, or as zone dedicated volt-free outputs. Relay programming is via dipswitches. This allows one zone from the control panel to activate multiple relays, up to a maximum of four, or a combination of zones and relays E.g. Zone 1-all four relays, or Zone 1-two relays, plus zone 3-one relay, and zone 4-one relay.

## Data

### Main Features:

### Contact rating:

### Contact material:

### Coil Consumption:

### Operate/Release:

### Temperature Range:

### Recommended interconnecting cable:

SPDT Contacts.

Dielectric strength 2.1kV dc contact to coil.

Contacts with a creepage distance of 11mm minimum.

UL, CUR file E43203

SPCO 15A @ 240Vac / 24Vdc

Silver Tin Oxide

203mW

10ms / 5ms (with no coil suppression)

-40°C to 70°C

Belden B8723

Screened Twisted Pair.

### Dimensions:

Height 123mm

Width 120mm

Depth 55mm